

## Product Features

- 32 Channel 4 IN 1 1080P High Definition Hybrid DVR
- 32 CH 1080P / 1080P Lite / 720P / WD1 recording
- Adopt standard H.264 high profile compression format to get high-quality video at much lower bit rate
- HDMI 1080P output, true high resolution display
- 16 CH simultaneously playback
- Support 4 SATA Hard Drive-Maxmium 24TB stroage capacity



# 32 Channel 1080P High Definition 4 IN 1 Hybrid DVR

## QTH322

### Technical Specifications:

Model	QTH322
<b>System</b>	
Compression	Standard H.264 High Profile
CPU	Cortex A9
OS	Embedded Linux
<b>Video</b>	
Video Input	BNC × 32
Resolution	TVI / CVI / AHD 1080P, 720P, WD1 real time
Output	HDMI × 1 : 1920 × 1080, VGA × 1 : 1920 × 1080, BNC × 1 : CVBS ( used as the main or spot output )
<b>Audio</b>	
Input	RCA × 4
Output	RCA × 1
Two-way audio	Take up channel one audio input
<b>Record</b>	
Resolution	1080P, 1080P lite, 720P, WD1
Frame Rate	1080P : 12 fps (PAL) / 15 fps (NTSC) 1080P lite / 720P / WD1 : 25 fps (PAL) / 30 fps (NTSC)
Bit Rate	768Kbps ~ 8Mbps
Mode	Manual, timer, motion, sensor
<b>Playback</b>	
Playback	16 CH

Playback	
Playback	16 CH
Search	Time slice / time / event / tag search
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
Function	Play, pause, FF, FB, digital zoom, etc.
Alarm	
Mode	Manual, sensor, motion, exception
Input	4
Output	1
Triggering	Record, snap, preset, e-mail, etc.
Network	
Interface	RJ45 10M / 100M / 1000Mbps × 1
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Web Client	Multiple users online
Mobile Device	
OS	iOS, Andriod
Storage	
HDD	SATA ×4
Backup	
Local Backup	U disk, USB mobile HDD
Network Backup	Yes
Port	
RS485	RS485 × 1, connect to PTZ or keyboard
USB	USB 2.0 × 1 ( front panel ), USB 3.0 × 1 ( rear panel )
Remote Controller	Optional
Others	
Power Supply	ATX 250W
Consumption	≤ 20W ( without HDD )
Work Environment	-10 ~ 50 ℃ , 10% ~ 90% humidity