

Product Features

- 16 Channel AHD/ TVI / CVI / ANALOG 4 IN 1 1080P High Definition Hybrid DVR
- 16 Channel AHD/ TVI / CVI / ANALOG 2.0 video input
- 16 Channel 1080P / 1080P lite / 720P / WD1 recording
- Adopt standard H.264 high profile compression format to get high-quality video at much lower bit rate
- HDMI 1080P output, true high resolution display
- Support 1 SATA HDDs up to 6TB, RS485, connect to PTZ or keyboard



16 Channel High Definition 1080P 4 IN 1 Hybrid DVR

QTH916

Technical Specifications:

Model	QTH916
System	
Compression	Standard H.264 High Profile
CPU	Cortex A7
OS	Embedded Linux
Video	
Video Input	BNC × 16
Resolution	AHD/ TVI / CVI / ANALOG: 1080P, 720P, WD1 real time
Output	HDMI × 1 : 1920 × 1080, 1280 × 1024, 1024 × 768 BVGA × 1 : 1920 × 1080, 1280 × 1024, 1024 × 768
Audio	
Input	RCA × 1
Output	RCA × 1
Two-way audio	Take up channel one audio input
Record	
Resolution	1080P, 1080P lite, 720P, WD1
Frame Rate	1080P : 12 fps (PAL) / 15 fps (NTSC) 1080P Lite / 720P / WD1 : 25 fps (PAL) / 30 fps (NTSC)
Bit Rate	768Kbps ~ 8Mbps
Mode	Manual, timer, motion, sensor
Playback	

Playback	16 CH
Search	Time slice / time / event / tag search
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
Function	Play, pause, FF, FB, digital zoom, etc.
Alarm	
Mode	Manual, sensor, motion, exception
Input	No
Output	No
Triggering	Record, snap, preset, e-mail, etc.
Network	
Interface	RJ45 10M / 100Mbps × 1
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Web Client	Max multiple users online
Mobile Device	
OS	iOS, Andriod
Storage	
HDD	SATA × 1, max 6TB per
Backup	
Local Backup	U disk, USB mobile HDD
Network Backup	Yes
Port	
RS485	RS485 × 1, connect to PTZ or keyboard
USB	USB 2.0 × 1 (front panel), USB 3.0 × 1 (rear panel)
Remote Controller	Optional
Others	
Power Supply	DC12V
Consumption	≤ 8W (without HDD)
Dimensions (mm)	300 × 248 × 52 (W × D × H)
Work Environment	-10 ~ 50 ℃ , 10% ~ 90% humidity